

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/009519 A1

(51) International Patent Classification⁷: **A61M 5/32**

(21) International Application Number:
PCT/IB2004/051319

(22) International Filing Date: 28 July 2004 (28.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/491,196 31 July 2003 (31.07.2003) US
60/519,724 14 November 2003 (14.11.2003) US

(71) Applicant (for all designated States except US): **SID TECHNOLOGIES LLC** [US/US]; 2033 Trowbridge Drive, Newtown, Pennsylvania 18940 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LAVI, Gilad**


[IL/US]; c/o 2033 Trowbridge Drive, Newtown, Pennsylvania 18940 (US). **TSALS, Izrail** [US/US]; C/o 2033 Trowbridge Drive, Newtown, Pennsylvania 18049 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: **SYRINGE WITH AUTOMATICALLY TRIGGERED SAFETY SLEEVE**



(57) Abstract: A medical injection device is provided which includes a shield system and a syringe. The shield system includes a housing (100), a shield (200) telescopically received in the housing (100) and slidably coupled to the housing (100) and a driver (300) that pushes the syringe stopper (510) to cause drug injection. The driver (300) is equipped with sensing elements (342) that automatically detect empty syringe. A spring (400) resiliently urges the shield (200) from a retracted position to an extended position shielding the needle (530). The syringe is coupled to the housing (100). The shield (200) is positioned externally to the syringe and the driver (300). The shield (200) includes flexible latches (210) to keep its position relative to the housing during storage and use. The axial movement of the driver (300) in respect to the syringe causes an automatic release of the spring (500) by sensors (342) when the syringe is empty, allowing the spring (500) to move and lock the shield (200) in the extended position after use.

WO 2005/009519 A1



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.